

Creating Value Through Innovation

## Polychem

GAT NO: 399/1-2,PLOT NO 5 ,VILLAGE-BHARE,POST-GHOTAWADE,TALUKA,MULSHI,DISTRICT- PUNE - 412115 Cell No: +91-9850834579,Email: information@polychem.co.in website: www.polychem.co.in

PRODUCT DATA SHEET 1.IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY	
SPECIAL FEATURES	<ul> <li>Muscle cool 771 is all purpose chlorine free cutting oil with good lubricity .</li> <li>It is blend of highly refined mineral oil emulsifiers , corrosion inhibitors with good antibacterial property .</li> <li>It contains extraordinary antibacterial additives</li> <li>It is having an excellent anticorrosive property over a wide dilution range.</li> <li>As it is oil based , it provides excellent lubricity to different parts of the machine &amp;elevates tool life considerably.</li> <li>It can be used for machining of all metals like SS,MS, C.I &amp; their alloys .</li> <li>This product does not contain toxic elements like Sulphur &amp; chlorine so water pollution problem do not occur .</li> </ul>
DILUTION	It is to be used 5 % with water.
APPLICATIONS	<ul> <li>Musclecool 771 is being used in quantity as soluble oil for all machine operations including grinding, turning, milling.</li> </ul>
TECHNICAL DATA	<ul> <li>Appearance :- Fluorescent green liquid</li> <li>Odour :- Characteristic odour</li> <li>Specific Gravity at 40°C:- 1.0 (±0.1)</li> <li>pH value of 5% solution [IS: 4955 –1978] :- 10 (±0.5)</li> <li>Solubility in water :- Soluble</li> <li>Flash Point (OPEN CUP) [ASTM D 92 ]:- N/A</li> <li>Refractometer Factor : 1.3 %</li> </ul>
PACKING & STORAGE	<ul> <li>210 LITS PLASTIC BARREL. &amp; Store in a cool, dry, well ventilated place. Use properly labeled and closable containers. Avoid direct sunlight, heat sources, and strong oxidizing agents.</li> </ul>

**SAFETY INFORMATION:** - Although this product does not pose a significant hazard to health a good standard of hygiene and housekeeping should be protected when using all type of industrial safety materials. Refer MSDS of the product.