

POLYCHEM

GAT NO: 399/1-2,PLOT NO 5 ,VILLAGE-BHARE,POST-GHOTAWADE,TALUKA,MULSHI,DISTRICT- PUNE - 412115

Cell No: +91-9850834579,Email: information@polychem.co.in website: www.polychem.co.in

PRODUCT DATA SHEET		
1.IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY		
NAME OF THE PRODUCT	POLYRUSTOP (IMP)	
SPECIAL FEATURES	<ul style="list-style-type: none"> POLYRUSTOP (IMP) is a water based preventive having blend of mineral oil, emulsifiers, corrosion inhibitors. It contains extraordinary antibacterial additives. These additives prevent bacterial growth thereby enhancing coolant life. It is having an excellent anticorrosive property over a wide dilution range. As it is oil based, it provides excellent lubricity to different parts of the machine and elevates tool life considerably. No skin irritation. 	
DILUTION	<ul style="list-style-type: none"> 12% to 25% with Soft/RO/DM water. 	
RUST PREVENTION PERIOD	Dilution	Actual Life Indoor
	12%	8 weeks
	15%	12 weeks
	20%	16 weeks
	25%	24 weeks.
APPLICATIONS	<ul style="list-style-type: none"> For Rust Prevention Dipping Application 	
TECHNICAL DATA	<ul style="list-style-type: none"> Appearance: - Brown Liquid. Odour: - Characteristic odour. Specific Gravity@40°C :- 0.9(+/-0.1) pH of 5 % solution [IS: 4955 –1978] :- 9 (+/- 1) Solubility in water :- Dispersible 	
MACHINING OF	<ul style="list-style-type: none"> Cast Iron M.S. 	
PACKING & STORAGE	<ul style="list-style-type: none"> 210 LITS PLASTIC BARREL. & Store in a cool, dry, well ventilated place. Use properly labeled and closable containers. Avoid direct sunlight, heat sources, and strong oxidizing agents. 	

SAFETY INFORMATION: - Although this product does not pose a significant hazard to health a good standard of hygiene and housekeeping should be protected when using all type of industrial safety materials. Refer MSDS of the product.