

## VICTORY POLYCHEM PVT LTD

GAT NO: 399/1-2,PLOT NO 5 ,VILLAGE-BHARE,POST-GHOTAWADE,TALUKA,MULSHI,DISTRICT- PUNE - 412115  
Cell No: +91-9850834579,Email: information@polychem.co.in website: www.polychem.co.in

### PRODUCT DATA SHEET

#### 1.IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY

<b>NAME OF THE PRODUCT</b>	<b>POLY AT-10 (Air Tool Oil)</b>
<b>SPECIAL FEATURES</b>	<ul style="list-style-type: none"> <li>• Lubricates, cleans and protects</li> <li>• Stops and inhibits rust</li> <li>• Repels airline moisture and water spray</li> <li>• Removes gummy deposits</li> <li>• Improves tool performance</li> <li>• Provides smoother operation</li> <li>• Extends tool life</li> <li>• Reduces maintenance and replacement costs</li> <li>• Contains Metal Treatment</li> <li>• POLY MT-10 technology for increased lubricity and boundary film lubrication</li> </ul>
<b>DILUTION</b>	<ul style="list-style-type: none"> <li>• Shake container or mix product lightly.</li> <li>• Use according to air tool manufacturer's Instructions. Tools may need lubricated daily, or several times a day, depending on their Frequency of use.</li> <li>• NOTE: All petroleum oils have a tendency to Cause natural rubber O-rings to swell.</li> <li>• Before using POLY AT-10 check with the tool manufacturer to make sure your air Tools utilize quality, non-rubber (i.e. Neoprene, Buna-N, Viton, etc.) O-rings.</li> </ul>
<b>APPLICATIONS</b>	<ul style="list-style-type: none"> <li>• Recommended for all piston- and rotary-type air tools, such as:</li> <li>• Impact and ratchet wrenches</li> <li>• Nailers and staplers</li> <li>• Sanders, grinders and polishers</li> <li>• Paving breakers</li> <li>• Screw drivers</li> <li>• Hammers</li> <li>• Shears</li> <li>• Drills</li> <li>• Chisels</li> <li>• Saws</li> <li>• Riveters</li> <li>• Tampers</li> <li>• Rock drills</li> </ul>
<b>TECHNICAL DATA</b>	<ul style="list-style-type: none"> <li>• Appearance - Red liquid</li> <li>• Odour- Mild petroleum, hint of cinnamon</li> <li>• Boiling point - 409°F (209°C)</li> <li>• Auto ignition temperature .- - 469°F (243°C)</li> <li>• Flash point-282°F (139°C) D93</li> <li>• Density @ 15°C, g/cm3 -0.9558</li> <li>• API gravity @ 60°F-18.2</li> <li>• Lbs. per gal (U.S.)-. ~ 7.977</li> <li>• Vapour pressure -&lt; 0.810 PSI</li> <li>• Viscosity @ 40°C - 26.4 cSt D-445</li> <li>• Viscosity @ 100°C- 4.45 cSt D-445</li> <li>• Pour point- - 38°F (- 39°C)</li> <li>• Solubility-Insoluble (water)</li> </ul> <p>The above properties are typical values and do not Constitute a product specification.</p>
<b>PACKING &amp; STORAGE</b>	<ul style="list-style-type: none"> <li>• 16-oz. bottle (474 ml)</li> <li>• 1 &amp; 5 U.S. gallon containers (3.8 &amp; 18.9 L)</li> <li>• 55 U.S. gallon drum (208 L)</li> </ul>

**SAFETY INFORMATION:** - Although this product does not pose a significant hazard to health a good standard of hygiene and housekeeping should be protected when using all type of industrial safety materials. Refer MSDS of the product.

