

VICTORY POLYCHEM PVT LTD

GAT NO: 399/1-2,PLOT NO 5 ,VILLAGE-BHARE,POST-GHOTAWADE,TALUKA,MULSHI,DISTRICT- PUNE - 412115
Cell No: +91-9850834579,Email: information@polychem.co.in website: www.polychem.co.in

PRODUCT DATA SHEET

| 1.IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY | |
|---|---|
| NAME OF THE PRODUCT | POLYPAINT REMOVER |
| SPECIAL FEATURES | <ul style="list-style-type: none"> POLYPAINT REMOVER is water based Carbon cum paint removing and cleaning solution. It has an alkaline pH. It has an excellent paint removing property. Remove paints & Carbons from metal components, Effectively reaches in to crevices and narrow gaps. No after effect on cleaned areas. Due to special additives it is devoid of bacterial growth. Nontoxic & safe to handle. |
| DILUTION | <ul style="list-style-type: none"> Used AS it is solution. |
| APPLICATIONS | <ul style="list-style-type: none"> The painted machined components are to be dipped in concentrate solution at 75-80 °C for 60 min under air bubbling. This product has another important use remove Paints, grease, oil, dust, powder, light rust, metal or carbon particles deposited in machine component, engine parts, hardware chains, bearing etc. . After cleaning the components with solution the components should be washed with water. |
| TECHNICAL DATA | <ul style="list-style-type: none"> Appearance : Clear Colourless liquid Odour :- Characteristic odour Specific gravity:- 1.0 (+ 0.1) pH of solution:- 11.0 (+ 1) Solubility in water :- partially Soluble Boiling point :- 110 C |
| PACKING & STORAGE | <ul style="list-style-type: none"> 210 LITS PLASTIC BARREL. & Store in a cool, dry, well ventilated place. Use properly labeled and closable containers. Avoid direct sunlight, heat sources, and strong oxidizing agents. |

SAFETY INFORMATION: - Although this product does not pose a significant hazard to health a good standard of hygiene and housekeeping should be protected when using all type of industrial safety materials. Refer MSDS of the product.