

## VICTORY POLYCHEM PVT LTD

GAT NO: 399/1-2,PLOT NO 5 ,VILLAGE-BHARE,POST-GHOTAWADE,TALUKA,MULSHI,DISTRICT- PUNE - 412115  
Cell No: +91-9850834579,Email: information@polychem.co.in website: www.polychem.co.in

<b>PRODUCT DATA SHEET</b>	
<b>1.IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY</b>	
<b>NAME OF THE PRODUCT</b>	<b>POLY SL-10 OIL CAN LUBRICANT™</b>
<b>SPECIAL FEATURES</b>	<ul style="list-style-type: none"> <li>• A blend of high-quality, petrochemical products</li> <li>• Contains no PTFE, silicone, graphite,</li> <li>• Molybdenum or solid lubricants.</li> <li>• Long-lasting protection against rust &amp;</li> <li>• Corrosion</li> <li>• Protects against extreme humidity</li> <li>• environments</li> <li>• Quick lubricating &amp; penetrating action</li> <li>• Creeps into remote, inaccessible areas</li> <li>• Provides free-flowing protection</li> </ul>
<b>Direction for use</b>	<ul style="list-style-type: none"> <li>• Shake container well. Wipe off exposed</li> <li>• surfaces; apply P O L Y SL-10 Oil Can</li> <li>• Lubricant directly to areas to be lubricated.</li> <li>• Repeat in especially stubborn applications.</li> </ul>
<b>APPLICATIONS</b>	<ul style="list-style-type: none"> <li>• Metal mechanisms</li> <li>• Sleeve bearings</li> <li>• Metal-to-metal surfaces</li> <li>• Open gears</li> <li>• Chain drives</li> <li>• Steel cables</li> <li>• Drag lines</li> <li>• Couplings</li> <li>• Bushings</li> <li>• Linkages</li> <li>• Pulleys</li> <li>• Wheels</li> <li>• Hinges</li> <li>• Augers</li> <li>• Tools</li> </ul>
<b>TECHNICAL DATA</b>	<ul style="list-style-type: none"> <li>• Boiling Point. -&gt; 193o C</li> <li>• Flash Point - 110oC PMCC</li> <li>• Specific Gravity @ 60oF- 0.94</li> <li>• Vapour Density (Air = 1) - &gt; 5.0</li> <li>• Vapour Pressure (mm Hg)@ 20oC- 0.01</li> <li>• Evaporation Rate (Butyl Acetate=1) - &lt; 0.01</li> <li>• Viscosity (SUS) - &lt; 100</li> <li>• Timken Extreme Pressure OK Load -60+</li> <li>• Pour Point -- 3 5 o C</li> <li>• Odour - Mild petroleum</li> <li>• Colour - Milky amber</li> <li>• Appearance - Low viscosity liquid</li> <li>• Antirust corrosion inhibitive - Yes</li> <li>• Water resistant - Yes</li> <li>• Solubility in Water -Insoluble</li> </ul>
<b>PACKING &amp; STORAGE</b>	<ul style="list-style-type: none"> <li>• 25 litre, 50 litre, 100 litres</li> <li>• 205 litres M.S drum</li> </ul>

**SAFETY INFORMATION:** - Although this product does not pose a significant hazard to health a good standard of hygiene and housekeeping should be protected when using all type of industrial safety materials. Refer MSDS of the product.

