

VICTORY POLYCHEM PVT LTD

GAT NO: 399/1-2,PLOT NO 5 ,VILLAGE-BHARE,POST-GHOTAWADE,TALUKA,MULSHI,DISTRICT- PUNE - 412115
Cell No: +91-9850834579,Email: information@polychem.co.in website: www.polychem.co.in

PRODUCT DATA SHEET

1.IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY	
NAME OF THE PRODUCT	POLYSTAMP OIL 350
PRODUCT DESCRIPTION	<ul style="list-style-type: none"> POLYSTAMP OIL 350 is Straight oil, medium viscosity formulated with mineral oil, lubricity agents and EP additives.
SPECIAL FEATURES	<ul style="list-style-type: none"> POLYSTAMP OIL 350 is a used for stamping/drawing the components. POLYSTAMP OIL 350 is oil based and uses high quality additives resulting in low friction, faster heat dissipation and improved die life. After application it leaves behind a protective rust inhibiting layer. It is non-toxic, non-polluting and has excellent anti-corrosive additives. It provides an excellent protection to ferrous and non-ferrous components.
DILUTION	<ul style="list-style-type: none"> It is to be used as supplied.
APPLICATIONS	<ul style="list-style-type: none"> Normal and deep draw sheet metal pressings.
TECHNICAL DATA	<ul style="list-style-type: none"> Physical State: - Liquid at ambient temperature. Colour :- Dark Yellow to Brown Liquid Specific Gravity@40°C :- 0.800 (± 0.1) Flash Point°C :- 125 (+/-5) Viscosity at 40°C [cSt] :- 8 (+ 2)
PACKING & STORAGE	<ul style="list-style-type: none"> 210 LITS PLASTIC BARREL. & Store in a cool, dry, well ventilated place. Use properly labeled and closable containers. Avoid direct sunlight, heat sources, and strong oxidizing agents.

SAFETY INFORMATION: - Although this product does not pose a significant hazard to health a good standard of hygiene and housekeeping should be protected when using all type of industrial safety materials. Refer MSDS of the product.