

VICTORY POLYCHEM PVT LTD

GAT NO: 399/1-2,PLOT NO 5 ,VILLAGE-BHARE,POST-GHOTAWADE,TALUKA,MULSHI,DISTRICT- PUNE - 412115

Cell No: +91-9850834579,Email: information@polychem.co.in website: www.polychem.co.in

PRODUCT DATA SHEET

1.IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY	
NAME OF THE PRODUCT	POLYRUSP DW 1200
SPECIAL FEATURES	<ul style="list-style-type: none"> After Moisture removal it leaves behind a protective rust inhibiting layer. It is non-hazardous, non-toxic, and non-polluting and has excellent anti-corrosive additives. It provides an excellent protection to ferrous and non-ferrous components. Once the machined component is applied with POLYRUSP DW 1200 immediate action of POLYRUSP DW 1200 of protective film formation starts and rest of the care is taken by this rust preventive layer. Outdoor -In ordinary industrial atmosphere, the treated components will remain rust Free for 6 to 9month. Indoor – 18 month. Coverage area =215 m²/ liter
DILUTION	<ul style="list-style-type: none"> NO DILUTION
APPLICATIONS	<ul style="list-style-type: none"> POLYRUSP DW 1200 is very much useful for machined ferrous and non-ferrous components
METHOD OF APPLICATIONS	<ul style="list-style-type: none"> The machined components are directly dipped (spray or brush) into POLYRUSP DW 1200 and taken out. The Moisture from the components settles at the bottom and the film formation takes place. The components not having any moisture can also be dipped to get rust preventive coating (shot blasted castings). These components are ready for packing. Here there is no need to packing the product in VCI paper etc.
TECHNICAL DATA	<ul style="list-style-type: none"> Appearance :- Pale Yellow to brawn Liquid Odour :- Characteristic odour Specific gravity :- 0.8 (+/- 0.1) Solubility in water :- Insoluble Flash Point °C:- 80 (+/-5) Film Thickness : 4-5 micron Viscosity @40 °C :- 2 (+/-1) cst
PACKING & STORAGE	<ul style="list-style-type: none"> 210 LITS PLASTIC BARREL. & Store in a cool, dry, well ventilated place. Use properly labeled and closable containers. Avoid direct sunlight, heat sources, and strong oxidizing agents.

SAFETY INFORMATION: - Although this product does not pose a significant hazard to health a good standard of hygiene and housekeeping should be protected when using all type of industrial safety materials. Refer MSDS of the product.