

VICTORY POLYCHEM PVT LTD

GAT NO: 399/1-2, PLOT NO 5, VILLAGE-BHARE, POST-GHOTAWADE, TALUKA, MULSHI, DIST- PUNE - 412115

Cell No: +91-9850834579, Email: information@polychem.co.in website: www.polychem.co.in

PRODUCT DATA SHEET

| | |
|------------------------------|---|
| NAME OF THE PRODUCT | SYNRADICOOOL PREMIX WB (Water Base Engine Testing Coolant) |
| SPECIAL FEATURES | <ul style="list-style-type: none"> • This product meets the following standards – ASTM – D3306, ASTM-4656 • It is non-freezing point rust preventive engine coolant • Provides excellent rust protection for engine component's materials like Cast Iron, MS, SS, Cu, Cu alloys, brass & Solder • Aluminum • Excellent compatibility with elastomers such as Nitriles, EPDM, Neoprene & silicon etc. • Rust Protection: - 3 to 6 month in engine seal tight & close condition. |
| DILUTION | <ul style="list-style-type: none"> • Ready to use (Use Straight) |
| APPLICATIONS | <ul style="list-style-type: none"> • It prevents flash rusting & corrosion of metallic alloys for equipment storage • Provides effective vapor phase corrosion protection & pH Buffering. |
| TECHNICAL DATA | <ul style="list-style-type: none"> • Physical state: Liquid at ambient temperature. • Appearance :Clear to slight hazy with Bluish tinge • Boiling point °C [ASTM D 1120] :100 (+/-2) • Density @15.5°C g/cc [ASTM D 1122] : 1.000 (+/- 0.005) • Reserved alkalinity , ml [ASTM D 1121] : To Report • pH value [ASTM D 1287] : 7.5 to 11 • Freezing point , °C [ASTM D 3321] : - 4 (+/-1) • Chloride in ppm [ASTM D 3634] : 25 Max • Flash Point [ASTM D 93-18] : N.A |
| PACKING & STORAGE | <ul style="list-style-type: none"> • 210Kg PLASTIC BARREL. & Store in a cool, dry, well ventilated place. Use properly labeled and closable containers. Avoid direct sunlight, Heat sources, and strong Oxidizing agents. |

SAFETY INFORMATION: - Although this product does not pose a significant hazard to health a good standard of hygiene And housekeeping should be protected when using all type of industrial safety materials. Refer MSDS of the product.