

VICTORY POLYCHEM PVT LTD

GAT NO: 399/1-2,PLOT NO 5 ,VILLAGE-BHARE,POST-GHOTAWADE,TALUKA,MULSHI,DISTRICT- PUN 412115 Cell No: +91-9850834579,Email: information@polychem.co.in website: www.polychem.co.in

PRODUCT DATA SHEET 1.IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY	
SPECIAL FEATURES	 It is replacement to MTO and diesel. It is having alkaline pH It has an excellent cleaning property. It has an aqueous base; it provides good cleaning for all types of machined components. The compounds used are having an affinity towards grease, oil, dust etc. Due to aqueous medium the dirt particles are wetted and settled at the bottom, rather than remaining in the dispersed form. After cleaning the components with POLYCLEAN MT 218 (IMP) the components should not be washed with water. It has excellent corrosion inhibition property. It does not contain any objectionable toxic solvents like Kerosene, Alcohol et Due to special additives it is devoid of bacterial growth. Since it is water based, it does not have any fire hazards No skin irritation. Used for ferrous as well as non-ferrous components.
DILUTION	5-20% with Soft/DM/RO water
APPLICATIONS	Cleaning Of Any Type Of Component
TECHNICAL DATA	 Appearance: - Colourless Liquid to Pale Yellow Liquid Odour :- Characteristic odour Specific gravity at 29.5°C: -1.0(+/-0.1) pH of solution [IS: 4955 -1978]: -10(+/-0.5) Solubility in water: - Freely Soluble
PACKING & STORAGE	 210 LITS PLASTIC BARREL. & Store in a cool, dry, well-ventilated place. Use properly labeled and closable containers. Avoid direct sunlight, heat sources, and Strong oxidizing agents.

SAFETY INFORMATION: - Although this product does not pose a significant hazard to health a good standard of hygiene and housekeeping should be protected when using all type of industrial safety materials. Refer MSDS of the product.