

## **VICTORY POLYCHEM PVT LTD**

GAT NO: 399/1-2,PLOT NO 5 ,VILLAGE-BHARE,POST-GHOTAWADE,TALUKA,MULSHI,DISTRICT- PUNE - 412115 Cell No: +91-9850834579,Email: information@polychem.co.in website: www.polychem.co.in

PRODUCT DATA SHEET  1.IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY	
SPECIAL FEATURES	<ul> <li>It is replacement to MTO and diesel.</li> <li>It is having alkaline pH</li> <li>It has an excellent cleaning property.</li> <li>It has an aqueous base, it provides good cleaning for all types of machined components. The compounds used are having an affinity towards grease, oil, dust etc. Due to aqueous medium the dirt particles are wetted and settled at the bottom, rather than remaining in the dispersed form.</li> <li>After cleaning the components with POLYCLEAN MT the components should not be washed with plane water.</li> <li>It has excellent corrosion inhibition property.</li> <li>It does not contain any objectionable toxic solvents like Kerosene, Alcohol etc. Due to special additives it is devoid of bacterial growth.</li> <li>It is water based, it does not have any fire hazards</li> <li>No skin irritation</li> <li>Used for ferrous as well as non-ferrous components.</li> </ul>
DILUTION & TEMPERATURE	5-6 % with Soft water  It is used 30 to 70 °C
APPLICATIONS	<ul> <li>Ultrasonic Cleaning</li> <li>Washing machine Of Any Type of Component.</li> <li>Pressure Cleaning.</li> </ul>
TECHNICAL DATA	<ul> <li>Appearance: - Colourless Liquid to Pale Yellow Liquid.</li> <li>Odour :- Characteristic odour</li> <li>Specific gravity@29.5 °C :- 0.9 to 1.05</li> <li>pH of solution [IS: 4955 –1978] :- 10( +/- 1 )</li> <li>Solubility in water :- Freely Soluble</li> </ul>
PACKING & STORAGE	<ul> <li>210 LITS PLASTIC BARREL. &amp; Store in a cool, dry, well ventilated place. Use properly labeled and closable containers. Avoid direct sunlight, heat sources, and strong Oxidizing agents.</li> </ul>

**SAFETY INFORMATION:** - Although this product does not pose a significant hazard to health a good standard of hygiene and housekeeping should be protected when using all type of industrial safety materials. Refer MSDS of the product.