

VICTORY POLYCHEM PVT LTD

GAT NO: 399/1-2,PLOT NO 5 ,VILLAGE-BHARE,POST-GHOTAWADE,TALUKA,MULSHI,DISTRICT- PUNE - 412115 Cell No: +91-9850834579, Email: information@polychem.co.in website: www.polychem.co.in

PRODUCT DATA SHEET 1.IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY	
SPECIAL FEATURES	 T.E.C 1260 isa soluble cutting oil having blend of mineral oil, emulsifiers, and corrosion inhibitors. It contains extraordinary antibacterial additives. It is stable up to 700 ppm hard water. These additives prevent bacterial growth thereby enhancing coolant life. It is having an excellent anticorrosive property over a wide dilution range. As it is oil based, it provides excellent lubricity to different parts of the machine andelevates tool life considerably. No skin irritation.
DILUTION	 5% with Ro/soft/ DM water. It can be use up to 700 ppm hard water.
APPLICATIONS	For metal cutting operations
	Cast IronM.S.Aluminum
TECHNICAL DATA	 Appearance: - Dark Yellow to Brown Liquid Odour: - Characteristic odour Specific gravity@29.5°C:-0.900(+/-0.1) pH of 5 % solution [IS: 4955 –1978]: - 9.0(+/-0.5) Solubility in water: -White Emulsion
PACKING & STORAGE	 35 LTRS & 210 LITS PLASTIC BARREL. & Store in a cool, dry, well-ventilated place. Use properly labeled and closable containers. Avoid direct sunlight, heat sources, and strong oxidizing agents.

SAFETY INFORMATION: - Although this product does not pose a significant hazard to health a good standard of hygiene and housekeeping should be protected when using all type of industrial safety materials. Refer MSDS of the product.